

POWERED BY **Dialog****Dialog eLink:** [Order File History](#)**Nut for ball bearing screws - has ball deviating path formed by contoured bosses forming groove edges****Patent Assignee:** OFF MEC SCARAVELLA**Inventors:** SCARAVELLA A**Patent Family (2 patents, 4 countries)**

Patent Number	Kind	Date	Application Number	Kind	Date	Update	Type
EP 103316	A	19840321	EP 1983201130	A	19830729	198413	B
IT 1153555	B	19870114	IT 198222897	A	19820819	198902	E

**Priority Application Number (Number Kind Date):** IT 198222897 A 19820819**Patent Details**

Patent Number	Kind	Language	Pages	Drawings	Filing Notes
EP 103316	A	EN	9	6	
Regional Designated States, Original	DE FR GB IT				

**Alerting Abstract:** EP A

The nut (1) for a ball bearing screw has a ball deviating guide to recirculate the balls from one thread to the adjacent one. The guide has a deviated path (11) for the balls (5), produced by bosses (13) on a body (9) insertable in the nut.

The deviated path has a first mouth (11) associated with a thread section (6) of the one thread and a second mouth (11) associated with a portion of the adjoining thread. The path can be a groove or an inner conduit (30) bored in the body. The bosses can have a cross-section corresponding to that of the balls.

**International Classification (Additional/Secondary):** F15B, F16H-025/22**Original Publication Data by Authority****European Patent Office**

Publication Number: EP 103316 A (Update 198413 B)

Publication Date: 19840321

**\*\*Mutter fuer Kugelumlaufspindel mit Kugelumlenkstueck** A nut for ball bearing screws having an improved ball deviating element  
**Ecran pour vis a billes ayant un element deviateur de billes\*\***

Assignee: OFFICINA MECCANICA SCARAVELLA ALFREDO F.LLI, Via Pavesi, 26, I-29100

Piacenza, IT (SCAR-N)

Inventor: Scaravella, Alfredo, Via Pavesi, 26, I-29100 Piacenza, IT

Agent: Giambrocono, Alfonso, Dr. Ing., et al, Ing. A. Giambrocono C. s.r.l. Via Rosolino Pilo, 19/b, I-20129 Milano, IT

Language: EN (9 pages, 6 drawings)

Application: EP 1983201130 A 19830729 (Local application)

Priority: IT 198222897 A 19820819

Designated States: (Regional Original) DE FR GB IT

Original IPC: F15B-0/00 F16H-25/22

Current IPC: F15B-0/00 F16H-25/22

Current ECLA class: F16H-25/22B2

Original Abstract: A nut for ball bearing screws having an improved ball deviating element. The nut (1, 17, 28) has conventionally an inside thread forming track for balls (5) and deviating elements for recirculating said balls from one thread to the adjoining one or for recirculating said balls from one thread to another spaced away thread along a substantially axial conduit bored in the nut. In order to prevent impacts of the circulating balls against the deviating element, said deviating element 8, 18, 18', 29) has a deviated path (11, 20, 20', 30) obtained by bosses (13, 13', 25, 25') forming edges (12, 12') of a S-shaped groove (11) or forming lead-in portions (24, 24') of an inner conduit (20, 20').

Claim: The nut (1) for a ball bearing screw has a ball deviating guide to recirculate the balls from one thread to the adjacent one. The guide has a deviated path (11) for the balls (5), produced by bosses (13) on a body (9) insertable in the nut. The deviated path has a first mouth (11) associated with a thread section (6) of the one thread and a second mouth (11) associated with a portion of the adjoining thread. The path can be a groove or an inner conduit (30) bored in the body. The bosses can have a cross-section corresponding to that of the balls.

### Italy

Publication Number: IT 1153555 B (Update 198902 E)

Publication Date: 19870114

Language: IT

Application: IT 198222897 A 19820819

Current ECLA class: F16H-25/22B2

Derwent World Patents Index

© 2008 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 2991202

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets

(11) Publication number:

**0 103 316**  
**A2**

(12)

# EUROPEAN PATENT APPLICATION

(21) Application number: 83201130.8

(51) Int. Cl.<sup>3</sup>: F 16 H 25/22

(22) Date of filing: 29.07.83

(30) Priority: 19.08.82 IT 2289782

(71) Applicant: **OFFICINA MECCANICA SCARAVELLA**  
**ALFREDO & F.LLI, Via Pavese, 26, I-29100 Piacenza (IT)**

(43) Date of publication of application: 21.03.84  
Bulletin 84/12


(72) Inventor: **Scaravella, Alfredo, Via Pavese, 26,  
I-29100 Piacenza (IT)**

(84) Designated Contracting States: DE FR GB IT

(74) Representative: **Giambrocono, Alfonso, Dr. Ing. et al,  
Ing. A. Giambrocono & C. s.r.l. Via Rosolino Pilo, 19/b,  
I-20129 Milano (IT)**

(54) A nut for ball bearing screws having an improved ball deviating element.

(57) The nut (1, 17, 28) has conventionally an inside thread forming track for balls (5) and deviating elements for recirculating said balls from one thread to the adjoining one or for recirculating said balls from one thread to another spaced away thread along a substantially axial conduit bored in the nut. In order to prevent impacts of the circulating balls against the deviating element, said deviating element (8, 18, 18', 29) has a deviated path (11, 20, 20', 30) obtained by bosses (13, 13', 25, 25') forming edges (12, 12') of a S-shaped groove (11) or forming lead-in portions (24, 24') of an inner conduit (20, 20').



EP 0 103 316 A2

A NUT FOR BALL BEARING SCREWS HAVING AN IMPROVED BALL BEARING  
DEVIATING ELEMENT.

The present invention relates to a nut for ball bearing screws having an improved ball deviating element.

5 The ball bearing screws, as known, comprise a nut and a shaft and a threading inside the nut and outside the shaft for accommodating a plurality of balls which are recirculated by means of deviating elements associated to the nut.

10 The ball bearing screws are of two types, i.e. a first type in which the deviating element provides for the recirculation of the balls from one thread to the adjoining one and a second type which comprises a pair of deviating elements for providing the recirculation of the balls from one thread to another spaced away thread along a substantially axial conduit bored in the nut.

15 The ball bearing screws are generally used where required to ensure the handling of mechanical means of considerable mass at high speed and accuracy, while assuring low friction coefficient and high reliability. A typical example as to the application of said mechanical means are the machine tools, and in particular computerised machine tools which have to operate  
20 with high level of accuracy.

In this field there is the trend to reduce the idle times between two successive working operations and this is done by increasing the displacement rate of the various components. Accordingly, the ball bearing screws are subjected to higher and  
25 higher speeds and, as a result, impacts would occur at those areas where a change in ball path is required, which impacts -if not suitably opposed- will lead to a ready and fast wearing of the ball bearing screw.

30 The deviating elements at present known comprise inserts positioned on the nut which are of complicated structure and comprise a plurality of parts to be secured on the outer surface of the nut.

35 The solutions hitherto proposed, in addition of being of complicated structure and proportionally expensive, have the drawback of not allowing a correct recirculation of the balls mainly due to shortage of edges along the deviated path, which shortage causes undesired impacts of the balls and fast wear of the assembly.

Another drawback of such conventional solutions resides in difficulty of assembling the deviating element to the nut, which is generally committed to pins, glueing or other mechanical fastening means.

5 It's an object of the present invention to provide a nut for ball bearing screws having an improved ball deviating element of such a configuration as to allow a sturdy connection of the inside nut threading and the deviated path, thereby substantially removing any cause of rapid wear in the assembly.

10 It's another object of the invention to provide a deviating element of such a configuration as to allow, in addition to the removal of impacts between balls and deviated path, also a rapid assembling without any need of using external elements.

15 The nut for ball bearing screws according to the invention could be of the type for recirculating the balls from one thread to the adjoining one or for recirculating said balls from one thread to another spaced away thread along a substantially axial conduit bored in the nut and is substantially characterised in that for the first type said ball deviating element has a deviated path  
20 for said balls as obtained by bosses provided on a body insertable in the nut, said deviating path having a first mouth associated with a thread portion of said one thread and a second mouth associated with said adjoining thread and characterised in that for the second type there are provided a pair of deviating elements each having an inner conduit with a mouth exiting  
25 in the respective thread and a mouth exiting in the axial conduit, each inner conduit being obtained by bosses provided on a body insertable in the nut.

30 One way for carrying out the invention is described in detail below with reference to the drawings which illustrate three embodiments, in which:

- Fig. 1 is a cross-sectional view of a first embodiment of a nut incorporating the improved ball deviating element of the invention, the recirculation of the balls being from one thread to the adjoining one;  
35

- Fig. 2 is a sectional view taken along line II-II of Fig. 1;

- Fig. 3 is a cross-sectional view of a second embodiment of a nut incorporating the improved ball deviating element of the invention, the recirculation of the balls being from one thread to another spaced away thread along a substantially axial conduit bored in the nut;  
40

- Fig. 4 is a sectional view taken along line IV-IV of Fig. 3;

- Fig. 5 is a cross-sectional view of a further embodiment of the invention substantially globating the embodiments of Figs.

1-4; and

- Fig. 6 is a sectional view taken along line VI-VI of Fig.

5.

5 With particular reference to Figs. 1 and 2, a nut -generally shown at 1- comprises a tubular steel body 2 having a threading conventionally formed in its internal surface including a continuous rounded bottom thread 3 having edges 4 and 4' for the sliding of a plurality of balls 5. The thread depth is less than the balls' diameter, whereby the latter are free to cooperate with a corresponding threading on a shaft (not shown) making up, together with the nut, the ball bearing screw assembly. As above mentioned, such a structure is within the prior art and therefore is no part of the present invention.

15 At two adjoining thread portions 6 and 6', said body 2 has a through hole 7 for the exact housing of a improved deviating element according to the invention and generally shown at 8.

20 The element 8 is formed by a body 9 having, when housed in said hole 7, a smooth external surface 10 arranged flush with the external surface of the body 2 and an internal surface having a substantially S-shaped groove 11 with a bottom 11', as shown in Fig. 1, lower than the rounded bottom 3 of the inside threading of the nut.

25 The groove 11 is defined by two opposite edges 12 and 12' arranged as continuation respectively of the edges 4 and 4' of said two adjoining thread portions 6 and 6', said edges 12 and 12' being obtained by providing the internal surface of the deviating element 8 with cylindrical bosses 13 and 13' of a cross-section corresponding to the section of the threading provided on the outer surface of the shaft, said bosses 13 and 13' being arranged in alignment with the thread portions 6 and 6' respectively so as to form mouths 11' and 11".

35 As shown in Figs. 1 and 2, the leading portions of the cylindrical bosses 13 and 13' project beyond the body 9 to be accommodated within the inoperative branches 14 and 14' of the thread portions 6 and 6'. The body 9 also has side extensions 15 and 15' intended to bear on the ridges 16 and 16' joining alternate thread portions 6 and 6'.

40 With particular reference to Figs. 3 and 4, the invention concept of making edges along the deviated path is applied to a nut, generally shown at 17, for the recirculation of the balls 5 from one thread to another spaced away thread along a substantially axial conduit bored in the nut.

The nut 17 is provided with two deviating elements, generally shown at 18 and 18', superimposed and respectively cooperating with a first thread 19 and a second thread 19'.

5 Each deviating element 18 and 18' has an inner conduit 20 and 20', the conduit 20 having a mouth 21 exiting in the first thread 19 and a mouth 22 exiting into one end of an axial conduit 23 bored in the nut 17 and the conduit 20' having a mouth 21' exiting in the second thread 19' and a mouth 22' exiting into the other end of the axial conduit 23.

10 The lead-in portions 24 and 24' of the mouth 21 and 21' are bored into cylindrical bosses 25 and 25' corresponding to the bosses 13 and 13' of the embodiment shown in Figs. 1 and 2.

15 By this arrangement, the incoming balls 5 are impactless guided along said lead-in portions 24 and 24' to enter the axial conduit 23.

As shown in Figs. 3 and 4, the leading portions of bosses 25 and 25' project beyond the elements 18 and 18' to be accommodated within the inoperative branches 26 and 26' of the thread portions 19 and 19', respectively. Also in this case side retreating extensions 27 are provided.

20 It clearly appears from the foregoing that the bosses 13, 13' of Figs. 1 and 2 and the bosses 25, 25' of Figs. 3 and 4 make up a thickness for forming the edges 12, 12' and the lead-in portions 24, 24' so that the groove 11 of Figs. 1 and 2 and the conduits 25 20, 20' of Figs. 3 and 4 can be correctly joined to the relative thread portions, and thus avoiding any possible risk of impact of the balls 5 during recirculation. Additionally, owing to the particular cross-section thereof, the cylindrical bosses will cooperate with the shaft's threading ensuring, together with the 30 side extensions 15, 15' and 27, a correct and steady positioning of the deviating elements in the nut.



The inventive concept of making edges along the deviated path has been also applied to a nut, generally shown at 28 in Figs. 5 and 6 wherein the parts corresponding to those of Figs. 1 and 35 2 are indicated with the same reference numerals. In this embodiment, as the one shown in Figs. 1 and 2, the nut 28 is provided with a deviating element 29 providing for the recirculation of the balls 5 from one thread to the adjoining one and differs from the deviating element 8 in that it is provided, instead than 40 the groove 11, with an inner conduit 30 bored in the same deviating element 29.



Claims:



1. A nut for ball bearing screws of the type comprising a ball deviating element for recirculating said balls from one thread to the adjoining one, characterised in that said ball deviating element (8, 29) has a deviated path (11, 30) for said balls (5) obtained by bosses (13, 13') provided on a body (9) insertable in said nut (1, 28), said deviated path having a first mouth (11') associated with a thread portion (6) of said one thread and a second mouth (11'') associated with a portion (6') of said adjoining thread.
2. A nut according to claim 1, characterised in that said deviated path is a groove (11).
3. A nut according to claim 1, characterised in that said deviated path is an inner conduit (30) bored in said body (9).
4. A nut according to claim 1, characterised in that said bosses are edges (12, 12') for said deviated path.
5. A nut according to claim 1, characterised in that said bosses are of cross section substantially corresponding to the sliding track of said balls.
6. A nut for ball bearing screws of the type comprising a pair of superimposed ball deviating elements for recirculating said balls from one thread to another spaced away thread along a substantially axial conduit bored in the nut, characterised in that each ball deviating element (18, 18') has an inner conduit (20, 20') having a mouth (21, 21') exiting in the respective thread and a mouth (22, 22') exiting in said axial conduit (23), said inner conduit being obtained by bosses (25, 25') provided on a body insertable in said nut (17).
7. A nut according to the preceding claims, characterised in that the leading portions (24, 24') of the bosses project beyond the body (9) to be accommodated within the inoperative branches (26, 26') of the thread.
8. A nut according to the preceding claims, characterised in that the body has side extensions (15, 15', 27) bearing on the ridges (16, 16') joining adjacent thread portions.



1/2







⑫

**EUROPEAN PATENT APPLICATION**

②① Application number: 83201130.8

⑤① Int. Cl.: **F 16 H 25/22**

②② Date of filing: 29.07.83

③① Priority: 19.08.82 IT 2289782

⑦① Applicant: **OFFICINA MECCANICA SCARAVELLA**  
**ALFREDO & F.LLI, Via Pavese, 26, I-29100 Piacenza (IT)**

④③ Date of publication of application: 21.03.84  
Bulletin 84/12

⑦② Inventor: **Scaravella, Alfredo, Via Pavese, 26,**  
**I-29100 Piacenza (IT)**


⑧④ Designated Contracting States: **DE FR GB IT**

⑧⑧ Date of deferred publication of search  
report: 09.01.85 Bulletin 85/2

⑦④ Representative: **Giambrocono, Alfonso, Dr. Ing. et al,**  
**Ing. A. Giambrocono & C. S.r.l. Via Rosolino Pilo 19/B,**  
**I-20129 Milano (IT)**

⑤④ **A nut for ball bearing screws having an improved ball deviating element.**

⑤⑦ The nut (1, 17, 28) has conventionally and inside thread forming track for balls (5) and deviating elements for recirculating said balls from one thread to the adjoining one or for recirculating said balls from one thread to another spaced away thread along a substantially axial conduit bored in the nut. In order to prevent impacts of the circulating balls against the deviating element, said deviating element (8, 18, 18', 29) has a deviated path (11, 20, 20', 30) obtained by bosses (13, 13', 25, 25') forming edges (12, 12') of a S-shaped groove (11) or forming lead-in portions (24, 24') of an inner conduit (20, 20').





European Patent  
Office

# EUROPEAN SEARCH REPORT

0103316

Application number

EP 83 20 1130

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. <sup>3</sup> )
X	FR-A-2 306 381 (J. LUC) * page 2, lines 27-37; figures 1-4 *	1,2,4,5	F 16 H 25/22
X	FR-A-2 249 578 (LA TECHNIQUE INTEGRALE) * page 3, paragraph 1; figures 1-5 *	1,3,5	
X	DE-B-2 437 497 (MANNESMANN) * column 6, lines 12-26; figures *	6,7	
A	GB-A- 879 462 (CAM GEARS LTD.) * whole document *	1,2,8	
A	FR-A-2 204 271 (LA TECHNIQUE INTEGRALE) * figures *	6,7	
A	US-A-3 161 073 (H.W. DEUTSCH et al.)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16-10-1984	Examiner MENDE H.
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			